Representation of Climate Impacts in GCAM

Leon Clarke


Workshop on Modeling Climate Change Impacts and Associated Economic Damages

Washington DC


Thursday, November 18, 2010



What is GCAM?



- Builds on the energy/economy model of Edmonds and Reilly completed three decades ago.
- Combines economics-based energy, agricultural models with an Integrated Climate Assessment Model (MAGICC).
- Dynamic-recursive model.
- Technologically detailed integrated assessment model.
- 14 geopolitical regions
- Emissions of 16 greenhouse gases and short-lived species: CO₂, CH₄, N₂O, halocarbons, carbonacious aerosols, reactive gases, sulfur dioxide.
- Runs through 2095 in 15-year time steps (moving to variable time steps).




What impacts would we want to consider in PNNL/JGCRI IA modeling?

- Goal #1: Pick things that are important.
- Goal #2: Pick things that involve interactions among the various systems represented in IA models
- Goal #3: Pick things that we actually have a chance of doing.
- Expanding on #3: A primary benefit of IA models is their ability capture interactions between systems. This leads to a perspective on impacts in which we distinguish between
 - Those which are most amenable to an integrated perspective.
 - Those which can "hang" off of the model and not feed back to other systems in the model.
- ► Although integrated analysis brings impacts together in an integrated system, aggregating and monetizing all impacts is not inherently core to considering impacts in GCAM.



A Plan for Impacts in PNNL/JGCRI's IA Modeling


- Near-term priorities;
 - Agriculture, Forestry, Land Use and Land Cover
 - Energy Use
 - Ocean Acidification
- High priorities with substantial model development necessary
 - Water Resources
 - Sea-Level Rise and Coastal Impacts
 - Human Health and Demographics
- Of substantial interest, but not easily quantifiable within existing IA models
 - Extreme Events and Thresholds
 - Biodiversity





A Plan for Impacts in PNNL/JGCRI's IA Modeling

- There are many ways to pursue these impacts:
 - One dimension
 - All in GCAM.
 - Linkages to other models (iESM, regional initiatives).
 - Another dimension
 - Endogenous interactions within the model – feedbacks with other systems.
 - "Hanging" off of GCAM.






Land Use Impacts


GCAM Moving to an Agro Ecological Zone Formulation for AgLU

OPTIONS FOR FEEDBACK

- Link results from ecosystem models (EPIC/BIOME/CENTURY) and ESMs to GCAM by changing parameters.
- Use sensitivity studies to begin to develop a concept of the scale of impacts in the context of integrated assessment and adjust GCAM parameters.
- Develop a reduced-form representation of ecosystem processes and response to climate change in GCAM.




Synthesis of process-level impact studies






Climate impacts interact with mitigation policy.



Impact of Impacts on Costs of Mitigation






Energy Impacts


Effects of Changing Degree Days on Building Energy Consumption: The Reference Case of China Buildings

Fixed HDD of 2158 Fixed CDD of 1046



1990 2005 2020 2035 2050 2065 2080 2095


HDD decreasing from 2158 to 1458 CDD increasing from 1046 to 1746




Other Long-Term Options: (1) Feedbacks on power plant efficiencies, (2) Feedbacks on water supply for hydroelectric power.





Water




GCAM: U.S. Energy System Results










Examples of Linkages between Platforms: iESM

A Research Collaboration Between Three National Laboratories: PNNL, ORNL and LBNL





Three Primary Tasks

- Create a first generation integrated Earth System Model (iESM) with both the human components of an IAM and a physical ESM;
- Further develop components and linkages within the iESM and apply the model to improve our understanding of the coupled physical, ecological, and human system;
- Add realistic hydrology, including freshwater demand, allocations, and demands to hold stocks of water as well as representations of freshwater availability from surface water, ground water, and desalinization




iESM Phase 1 Initial Coupling Strategy









THE CLM: Initial One-way Coupling: Land Use and Land Cover Change (iESM Control experiment)




iESM multi-phase coupling strategy



Examples of Linkages between Platforms: Regional Initiative



Buildings Demand Modeling



BEND Model

- ~4000 buildings will be simulated in EnergyPlus to represent the buildings in the RGCAM U.S. test region:
 - 4 climate zones
 - 11 commercial building types
 - 3 residential building types
 - 6-9 sizes within each building type
 - 7-8 vintages of existing buildings and 3 vintages of new buildings
- Building characteristic vary for each combination of attributes
- Hourly (8760 hours) electrical output used to calibrate models and determine building weights based on actual weather and actual hourly electric consumption for test region.
- Our challenge is to pass data back and forth between BEAMS and R-GCAM.

Discussion

Evergreen



